

(unit: mm)

Model	Size	A	B	C	D
TK4N	55	37	45 ^{+0.3} _{-0.2}	22 ^{+0.3} _{-0.2}	
TK4S	65	65	45 ^{+0.3} _{-0.2}	45 ^{+0.3} _{-0.2}	
TK4S (P)	65	65	45 ^{+0.3} _{-0.2}	45 ^{+0.3} _{-0.2}	
TK4M	90	90	68 ^{+0.7} _{-0.6}	68 ^{+0.7} _{-0.6}	
TK4H	65	115	45 ^{+0.3} _{-0.2}	92 ^{+0.3} _{-0.2}	
TK4W	115	65	92 ^{+0.3} _{-0.2}	45 ^{+0.3} _{-0.2}	
TK4L	115	115	92 ^{+0.3} _{-0.2}	92 ^{+0.3} _{-0.2}	

[illegible]

Input type		Decimal point	Display	Input range (°C)	Input range (°F)
Thermocouple	K (CA)	1	$\overline{E}CRH$	-200 to 1350	-328 to 2463
		0.1	$\overline{E}CRL$	-199.9 to 999.9	-199.9 to 999.9
	J (IC)	1	$\overline{J}IC.H$	-200 to 800	-328 to 1472
		0.1	$\overline{J}I.C.L$	-199.9 to 800.0	-199.9 to 999.9
	E (CR)	1	$\overline{E}C.r.H$	-200 to 800	-328 to 1472
		0.1	$\overline{E}C.r.L$	-199.9 to 800.0	-199.9 to 999.9
	T (CC)	1	$\overline{E}CC.H$	-200 to 400	-328 to 752
		0.1	$\overline{E}C.C.L$	-199.9 to 400.0	-199.9 to 752.0
	B (PR)	1	$\overline{b}Pr$	0 to 1800	32 to 3272
	R (PR)	1	$\overline{r}Pr$	0 to 1750	32 to 3182
	S (PR)	1	$\overline{s}Pr$	0 to 1750	32 to 3182
	N (NN)	1	$\overline{n}n.n$	-200 to 1300	-328 to 2372
	C (TT) ^{*1}	1	$\overline{C}t.t$	0 to 2300	32 to 4172
	G (TT) ^{*2}	1	$\overline{G}t.t$	0 to 2300	32 to 4172
	L (IC)	1	$\overline{L}I.C.H$	-200 to 900	-328 to 1652
0.1		$\overline{L}I.C.L$	-199.9 to 900.0	-199.9 to 999.9	
U (CC)	1	$\overline{U}CC.H$	-200 to 400	-328 to 752	
	0.1	$\overline{U}C.C.L$	-199.9 to 400.0	-199.9 to 752.0	
Platinel II	1	$\overline{P}L.t.t$	0 to 1390	32 to 2534	
RTD	Cu 50Ω	0.1	$\overline{C}U.5$	-199.9 to 200.0	-199.9 to 392.0
	Cu 100Ω	0.1	$\overline{C}U.10$	-199.9 to 200.0	-199.9 to 392.0
	JPt 100Ω	1	$\overline{J}Pt.H$	-200 to 650	-328 to 1202
		0.1	$\overline{J}Pt.L$	-199.9 to 650.0	-199.9 to 999.9
	DPT 50Ω	0.1	$\overline{d}Pt.5$	-199.9 to 600.0	-199.9 to 999.9
	DPT 100Ω	1	$\overline{d}Pt.H$	-200 to 650	-328 to 1202
		0.1	$\overline{d}Pt.L$	-199.9 to 650.0	-199.9 to 999.9
	Nickel 120Ω	1	$\overline{n}l.12$	-80 to 200	-112 to 392
Analog	Voltage	0-10V	$\overline{R}u.1$	-1999 to 9999 (Display point will be changed according to decimal point position.)	
		0-5V	$\overline{R}u.2$		
		1-5V	$\overline{R}u.3$		
		0-100mV	$\overline{R}\overline{n}.u.1$		
	Current	0-20mA	$\overline{R}\overline{n}\overline{R}.1$		
		4-20mA	$\overline{R}\overline{n}\overline{R}.2$		

DRW170598AB